



POLYURETHANE
MACHINERY CORPORATION

PREMIER

IDEAL FOR HIGH OUTPUT
RESIDENTIAL AND COMMERCIAL
APPLICATIONS

PREMIER is the most
technologically advanced
proportioner in the PMC line-up

PREMIER puts you in
complete control with intuitive
design and remote capabilities


PMC RELIABILITY MEETS THE FUTURE OF PLURAL COMPONENT PROPORTIONERS

KEY FEATURES:

- Up to **40 lbs per minute** Foam
- User management and traceability features
- **Touchscreen dashboard** - all controls at your fingertips
- Chemical management display insures that ratio, temperature and pressures are accurate
- Reporting software captures **data in real time** and can email daily reports
- Saves all historical data and alarms
- On-screen technical support
- System settings in English and Spanish
- **Remote access** from any web enabled device



MADE IN THE USA



POLYMAC-USA.COM

BUY THE BEST THE FIRST TIME.

WORLDWIDE HEADQUARTERS
One Komo Drive Lakewood, NJ 08701 USA
P: (732) 415-4400 | E: marketing@polymacusa.com

PREMIER



POLYURETHANE
MACHINERY CORPORATION



STANDARD FEATURES

Remote access proportioner from any web enabled device, without the need to download a specific app. Proportioner can be run remotely if desired.

User management and traceability features allow owners to create unique user ID's or a generic user for each function, i.e. operator, tech support, owner.

On-screen **technical support view** displays raw data to help diagnose issues.

Chemical management display ensures that ratio, temperature and pressures are accurate with user selectable setpoints for upper and lower limits.

Reporting software captures data in real time, and can be displayed on a graph for easy-to-see results or reports can be emailed directly from the machine.

TECHNICAL DATA

| MODEL | PREMIER |
|------------------------------------|--|
| Output* | 40 lbs/min (18.14 kg/min) |
| Max. Working Pressure..... | 2,000 psi (138 bar) |
| Max. Hose Length..... | 410 ft (121.9 m) |
| Heater Wattage | 18,000 watts (Dual htr) |
| Hose Heating Power | 120 volts |
| Max. Fluid Temp | 190 °F (87.7 °C) |
| Weight (Empty Hydraulic Tank)..... | 670 lbs (304 kg) |
| Weight (Full Hydraulic Tank)..... | 844 lbs (383 kg) |
| Electrical @ 18KW Heaters..... | 67 amps @ 3 x 230V |
| Dimensions (W x D x H)..... | 40in x 30in x 55in (102cm x 76cm x 140cm) |

*Output measured with mineral oil

ORDERING INFORMATION

| PART#..... | DESCRIPTION |
|----------------|--------------------------------|
| PREMIER | |
| 203011..... | PRMR,5HP,220V,3PH,RV,120T,18KW |

PMC LEGEND FOR MACHINE DESCRIPTIONS

PH-2.....Machine Series

3HP.....Horsepower (3hp, 5hp, 7.5hp)

230V.....Voltage (230v, 380v or 460v)

1PH.....Phase (Single or Three)

RV.....Recirculation Valves

90T.....Transformer Size (30V, 70V, 90V, or 120V)

10KW ... Heater Wattage

IM..... Inlet Monitoring

PBC Pressure Balance Control

DURABLE. RELIABLE. SMARTER.
OUR PRODUCTS OUTPERFORM & OUTLAST OUR COMPETITORS

BUY THE BEST
THE FIRST TIME
FIND A →
DISTRIBUTOR



POLYMAC-USA.COM